

Tec identity clean-room

(IS 2023_CLC) Work swivel chair with foot ring (Counter design),

without armrests, conductive.

Medium-high backrest with plastic outer shell, height-adjustable.

Specification:

- Work swivel chair (Counter design) with foot ring, without armrests (ISO-class still under review), conductive.

Area of use:

- For highly sensitive areas where the air in the room needs to be extremely clean.
- With mechanism SE; Manufacturer testing and approval for a user weight of up to 150 kg.

Design:

- Rüdiger Schaack.

Warranty:

- 5 years (Service life 220 working days/ year with 8 hrs./day), accordance with the warranty conditions.

Certification/ norms:

- Model has the GS label and meets the valid standard of EN 68877.
- ESD: Antistatic and conductive model to avoid the problems caused by electrostatic charging: The chairs comply with the static charge dissipation regulations set out in DIN EN 61340-5-1:2017; tested by LGA Nuremberg. Resistance $R_g \leq 1 \times 10^6 \Omega$.
- DIN EN ISO 9001:2015 (Quality management system).
- EMAS and DIN EN ISO 14001:2015 (Environmental policy).

Ecology:

- All materials are environmentally sound, easily separable, recyclable.

Mechanism(s):

Synco-Evolution® (SE NV T6): Synchronised mechanism with lateral infinite spring force adjustment and synchronised movement lockable in four positions. Seat-tilt adjustment (-4°). 6 cm seat-depth adjustment using sliding seat, can be locked in 6 positions.

Model colour/ Plastic parts:

- (KGS): Graphite black (RAL 9011). All plastic parts are of pure sort, free of PVC and recyclable.

Armrests:

- (A0): Model without armrests.

Base, type P (Ø 71 cm):

- (FPAPO): Aluminium die-cast pressure, polished.

Seat height/ Gas unit:

- (S67CR*): Seat height approx. 47-61 cm (chrome base tube), only in conjunction with glides (R10HGSL).
- Option(s) without surcharge:
 - (S64CR*): Seat height approx. 46-62 cm (chrome base tube) - for models with castors (R70WGSL/ R86WGSL).
- Option(s) against surcharge:
 - (S80CR*): Seat height approx. 62-87 cm (chrome base tube) - only in conjunction with soft castors (R86WGSL).
 - (S85CR*): Seat height approx. 62-87 cm (chrome base tube) - only in conjunction with glides (R10HGSL).

* PU: + 0,5 cm.

Castors / Glides (conductive):

- (R10HGSL): Plastic glides for soft floors, black - can also be used universally for hard floors - only in conjunction with gas unit S67CR/ S85CR.
- Option(s) without surcharge:
 - Load-dependent braked twin-wheel castors (covered):
 - (R70WGSL): Soft castors (Ø 50 mm) for hard floors, black- only in conjunction with gas unit S64CR/ S86GS.
- Option(s) against surcharge:
 - (R86WGSL): Load-dependent locking twin-wheel castors, covered (Ø 50 mm):
Soft castors for hard floors, black - only in conjunction with gas unit S64CR/ S80CR.

Upholstered version:

- Ergonomically shaped. Upholstered seat and backrest.
- Medium-high backrest with plastic outer shell, 7 cm height-adjustable.
- Backrest with black pushing handles as standard.
- Removable window, format: Avery Zweckform Typ L 7162 (99,1 x 33,9 mm).
- Option of model identification via colored plastic elements (back panel, identification ring above the star base).
- Two upholstered versions are available:
 - (SR): Upholstered seat and backrest. Breathable cut foam, CFC and CHC free.
 - (PU): Seat and backrest upholstered in hardwearing polyurethane (PU), black, anti-slip finish, with edge protection. Seat and backrest: Shore A 20 (+/- 5).

Description	Seat	Backrest
Foam thickness:	4,5 cm	3,0 cm
Foam density:	65 kg/ m ³	60 kg/ m ³
Cover:	unglued	unglued

Foot ring (Ø 53 cm):

- Infinitely height-adjustable with handwheel locking system.
- Chrome, with slip-resistant surface (as mounting aid).

Upholstery fabrics:

- A number of price groups with different upholstery fabrics and colours (see current price list and fabric catalogue).
- Price group "PU": Polyurethane soft, black (PUSGS).
- Price group "A": Madrid ID Itf.

Dimensions* (cm):

	Total	Seat	Backrest
Height*	116-148	62-87	54-61
Width:	71	46	46
Depth:	71	39-45	-

* All dimensions are approximate value and may vary depending on the particular specification of the model.
Output values for gas unit S80CR/ S85CR (look for more "Safety gas unit").

Weight*:

- approx. 15,3 kg (SR).
- approx. 16,3 kg (PU).

Packing:

- (V12): Model completely assembled in box.

ESD:

- Antistatic and conductive model to avoid the problems caused by electrostatic charging:
The chairs comply with the static charge dissipation regulations set out in DIN EN 61340-5-1:2001;



The product illustration shows an option with surcharge.

The Dauphin HumanDesign® Company reserves the right to effect technical amendments on the indicated features.
Date of last revision: 2024.12/ 02.



DAUPHIN
INDUSTRY

Tec identity

clean-room (IS 2023_CLC)

Labeling (ID):

tested by LGA Nuremberg. Resistance $R_g \leq 1 \times 10^6 \Omega$.

Awards:

- (ZIDRY): Labeling (ID) rape yellow (RAL 1021).

To use:

- AGR-seal of quality: „Aktion Gesunder Rücken e.V.“.

Cleanliness and functionality. Extreme care must be taken when furnishing clean-rooms. While emissions of even the smallest Particles must be extremely low, the furniture's ability to dissipate any electrostatic charges is usually an important requirement too. With their smooth surfaces, sealed upholstery, covered mechanisms and dissipative materials, our models developed for use in clean -rooms meet all of these requirements with ease.

However, our seating philosophy is also put into practice with the same care and attention. All of our products are oriented towards people and achieving a healthy seated posture. Responsible work in highly technical clean-rooms demands ergonomic perfection together with impeccable functionality.

