Tec adjust ESD

(IS 2176_ESD) Work swivel chair without armrests, conductive. High, flexible backrest with plastic outer shell, height-adjustable.

Specification:

- Work swivel chair without or with armrests, conductive.

Area of use:

- For all ESD areas
- With mechanism SE for people with a body weight of up to 150 kg.

Design

- Dauphin Design-Team.

Warranty:


 5 years (Service life 220 working days/ year with 8 hrs./day), accordance with the warranty conditions.

Certification/ norms:

- Model has the GS label and meets the valid standard of DIN 68877.
- DIN EN ISO 9001:2015 (Quality management system).
- EMAS and DIN EN ISO 14001:2015 (Environmental policy).

Ecology

All materials are environmentally sound, easily separable, recyclable.



locked in 6 positions

Model colour/ Plastic parts:

- (KGS): Graphite black (RAL 9011). All plastic parts are of pure sort, free of PVC and recyclable.

Armrests:

- (A319APO): 3F-Multifunctional armrests: 10 cm height adjustable, 5 cm width adjustable (without the use of tools using

eccentric closure) and 4 cm depth-adjustable. Armrest pads made of Polypropylen (PP).

Armrest posts aluminium polished, conductive.

Base, type P (Ø 71 cm):

- (FPAPO): Aluminium die-cast pressure, polished.

Seat height/ Gas unit: - (S64CR): 46-62

- (S64CR): 46-62 cm seat height (chrome base tube) - only in conjunction with castors.

- Option(s) against surcharge:

- (S67CR): 47-61 cm seat height (chrome base tube) - only in conjunction with glides.

Castors/ Glides, conductive:

- Load-dependent braked twin-wheel castors (covered).

- (R70WGSL): Soft castors (Ø 50 mm) for hard floors, black, conductive - only in conjunction with gas unit S64CR.

- Option(s) without surcharge:

- (R70HGSL): Hard castors (Ø 50 mm) for soft floors, black, conductive - only in conjunction with gas unit S64CR.

- (R10HGSL): Glides for soft floors, black, conductive - can also be used universally for hard floors- only

in conjunction with gas unit S67CR.

- Option(s) against surcharge:

- (R86WGSL): Load-dependent locking twin-wheel castors, covered (Ø 50 mm):

Soft castors for hard floors, black, conductive - only in conjunction with gas unit S64CR.

Upholstered version:

- Ergonomically shaped. Upholstered seat and backrest.

- High, flexible backrest with plastic outer shell, 7 cm height-adjustable, adjustable with left and

right hand while seating and follows the lateral movements.

- Upholstered backrest without lateral stitching.

- Breathable moulded foam (PU), free of CFC and CHC.

Seat	<u>Backrest</u>
5,5 cm	4,0 cm
65 kg/ m³	60 kg/ m³
unglued	glued
	5,5 cm 65 kg/ m³

Upholstery fabrics: - One number of price groups with different upholstery fabrics and colours (see current price list and fabric catalogue):

- Price group "A, conductive":

- "King" and "Madrid" (black imitation leather).

Dimensions* (cm):

	iotai	Seat	Backrest
Height*:	107-130	46-62	61-68
Width:	71	47	45
Depth:	71	38-44	-

* All dimensions are approximate value and may vary depending on the particular specification of the model (look for output values "Safety gas unit").

Weight: - approx. 15,0 kg (without armrests).

Packing: - (V00): Model completely assembled in protective cover (in the export markets on demand).

- Option(s) without surcharge:

- (V12): Model completely assembled in box.

ESD: - Antistatic and conductive model to avoid the problems caused by electrostatic charging:

The chairs comply with the static charge dissipation regulations set out in DIN EN 61340-5-1:2001;

tested by LGA Nuremberg. Resistance Rg \leq 1x10 6 Ω .

To use:

The range satisfies the exact requirements when it comes to ergonomics, timeless styling and ease of operation. In terms of design, the chairs are deliberately timeless and focus on your individual needs. And with just a few simple steps, you can adjust your chair so that even long periods of time spent sitting becomes a pleasure.



