# Industry Tec basic (Reinraum)

- (IS 1967) Mobile standing aid with foot ring.

#### Specification:

- Mobile standing aid with foot ring.

#### Area of use:

- For all time consuming work that can not be done sitting.

- Dauphin Design-Team.

#### Warranty:

- 5 years (Service life 220 working days/ year with 8 hrs./day), accordance with the warranty conditions.

#### Certification/ norms:

- Model has the GS label and meets the valid standard of EN 1335.
- DIN EN ISO 9001:2015 (Quality management system of the company).
  EMAS and DIN EN ISO 14001:2015 (Environmental policy of the company).

- Ergonomically shaped.
- Anti-slip surface made of hard wearing polyurethane (PU).
   seat-tilt adjustment up to -15°.

Description	Seat	
Foam thickness:	23 mm	
Foam density:	-	
Cover:	non-upholstered	

### Foot ring (Ø 46 cm):

- Infinitely height-adjustable with handwheel locking system.
- Chrome, with slip-resistant surface (as mounting aid).

#### Upholstery fabrics:

- Price groups "Plastic PU". Polyurethane black are available to choose from (see current price list and fabric catalogue).

#### Plastic components:

- Standard: Graphite black (RAL 9011).

- All plastic parts are of pure sort, free of PVC and recyclable.

- Standard: Type R1 (Ø 60 cm), plastic (polyamide, fibre-glass reinforced) graphite black (RAL 9011).
- only for standard gas unit.
- Option(s) against surcharge: Type R2 (Ø 65 cm): Aluminium die-cast pressure, polished.

## Seat height/ Gas unit (chrome base tube):

- Standard: Safety gas unit, seat height: S80CR for castors/ S85CR for glides: approx. 55-80 cm.

### Castors (Ø 50 mm):

- Load-dependent locking twin-wheel castors.
- Standard: Soft castors for hard floors, black.
- Option(s) without surcharge:
  Flat universal glides for hard and soft floors, black.



### Function/ Ergonomics:

- Seat height-adjustable, with anti-slip surface made of hard wearing polyurethane (PU).
   Seat-tilt adjustment up to -15°.
- Chrome, infinitely height-adjustable foot ring with quick-release mechanism and with slip-resistant surface (as mounting aid).

All materials are environmentally sound, easily separable, recyclable.

#### Dimensions\* (cm)

IS 1967	Total	Seat
Height:	69-94	55-80
Width:	60	37
Depth:	60	36

\* All dimensions are approximate values.

### Weight:

- approx. 8,8 kg.

#### Packing:

- Model completely assembled in protective cover (in the export markets on demand).
- Option(s) without surcharge:
- Model partly knocked down in box.
- Option(s) against surcharge:
- Model completely assembled in box.

